

LK-B420T

TT / DT label printer

Thermal transfer and direct thermal label printer for stable label printing with ribbon support.



Resolution: 203 DPI



Speed: 127 mm/s



Ribbon: up to 300 m



Media width: 25.4 - 118 mm

Key features



Resolution
203 DPI



Speed
127 mm/s



Ribbon
up to 300 m



Media width
25.4 - 118 mm



Interface
USB + Ethernet



BarTender
label software

Ideal for



Warehouse



Logistics



Supermarket



Labeling

Device views



Main view
device visual



Product detail
equipment view

Side view
device format



Printing

Type	Thermal transfer / direct thermal
Resolution	203 DPI
Print speed	127 mm/s
Maximum print width	108 mm
Maximum print length	2286 mm
Print head life	30 km



Media and ribbon

Media type	Continuous, gap, black mark, fanfold and perforated
Media width	25.4 - 118 mm
Media thickness	0.06 - 0.254 mm
Ribbon capacity	Max. 300 m
Ribbon width	110 mm

Physical data

Power	AC 100-240 V 1.8 A, DC 24 V 2.5 A, 60 W
Dimensions	302.5 x 234 x 194.8 mm
Weight	2.6 kg
Drivers / SDK	Windows / Linux / Mac / iOS

System and interfaces

Processor	32-bit CPU, 200 MHz RISC
Memory	8 MB SDRAM, 4 MB Flash, expansion up to 4 GB
Standard interface	USB + Ethernet 10/100 Mbps
Optional interface	USB + serial / LAN / Bluetooth / WiFi
Emulations	TSPL, EPL, ZPL, DPL